

STOPDIGGING!®



ADAPTER SCREW


The adapter screw has a mounting plate with a series of slots that allow for precise adjustment in several directions and is therefore suitable for structures requiring a great deal of accuracy. This model takes a wide range of attachments including the beam bracket, post bracket, plate and L-support which make it a very versatile support. There is almost nothing we cannot securely attach! This makes it ideal for a variety of structures such as living quarters on construction sites, sound dampening boards, greenhouses, solar cells and prefabricated houses.

The adapter screw is available in two different designs.



SGC	865	1200	1600	2000	2500
SCREW LENGTH	865 mm	1200 mm	1600 mm	2000 mm	2500 mm
OUTER DIAMETER	76 mm				
PLATE DIAMETER	200 mm				
COMPRESSION CAPACITY	13,5 kN	25,0 kN	35,0 kN	45 kN	55 kN
TENSILE CAPACITY	7,0 kN	12,5 kN	21,5 kN	41,5 kN	41,5 kN
LATERAL CAPACITY	3,5 kN	6,0 kN	8,5 kN	11,5 kN	14,5 kN

EXAMPLE OF USES AREAS



EXPECTED
MINIMUM
SERVICE LIFE
100
YEARS*



*StopDigging provides a generous warranty, which covers all ground screws and associated applications. During the warranty period, we guarantee that the screw retains its properties and performance. We also state an expected minimum service life for the products based on experience and research. This value is usually at the lower end of how long the screw in reality retains its performance, which depending on ground conditions can be several times higher. See full terms and conditions in the current warranty document.